

## Fixture Report

Project: Christmas 2017 Stage Design

Drawing author: Chris Monson

Drawing version: 1.3

### Fixtures

Unit	Channel	Fixture	Optics	Circuit	Patch	Mode	Filters Gobos	Accessories
1	0	Robe ColorWash 575E AT Zoom	Fresnel Lens, 8° - 50°		B.5	Mode 1, 19 chs		
2	0	Robe ColorWash 575E AT Zoom	Fresnel Lens, 8° - 50°		B.24	Mode 1, 19 chs		
3	0	Robe ColorWash 575E AT Zoom	Fresnel Lens, 8° - 50°		B.43	Mode 1, 19 chs		
4	0	Robe ColorWash 575E AT Zoom	Fresnel Lens, 8° - 50°		B.62	Mode 1, 19 chs		
5	0	Robe ColorSpot 575E AT	Standard, 15° - 22°		C.19	Mode 1, 27 chs		
6	0	Robe ColorSpot 575E AT	Standard, 15° - 22°		D.10	Mode 1, 27 chs		
7	0	Robe ColorSpot 575E AT	Standard, 15° - 22°		E.10	Mode 1, 27 chs		
8	0	Robe ColorSpot 575E AT	Standard, 15° - 22°		F.10	Mode 1, 27 chs		
9	0	Robe ColorSpot 575E AT	Standard, 15° - 22°		C.46	Mode 1, 27 chs		
10	0	Chauvet Intimidator Wash Zoom 350 IRC	Standard Lens, 14° - 58°		C.73	Advanced Mode, 29 chs		
11	0	Chauvet Intimidator Wash Zoom 350 IRC	Standard Lens, 14° - 58°		C.102	Advanced Mode, 29 chs		
12	0	Chauvet Intimidator Wash Zoom 350 IRC	Standard Lens, 14° - 58°		D.37	Advanced Mode, 29 chs		
13	0	Chauvet Intimidator Wash Zoom 350 IRC	Standard Lens, 14° - 58°		D.66	Advanced Mode, 29 chs		
14	0	Chauvet Intimidator Wash Zoom 350 IRC	Standard Lens, 14° - 58°		D.95	Advanced Mode, 29 chs		
15	0	Chauvet Intimidator Wash Zoom 350 IRC	Standard Lens, 14° - 58°		D.124	Advanced Mode, 29 chs		
16	0	Chauvet Intimidator Wash Zoom 350 IRC	Standard Lens, 14° - 58°		E.37	Advanced Mode, 29 chs		
17	0	Chauvet Intimidator Wash Zoom 350 IRC	Standard Lens, 14° - 58°		E.66	Advanced Mode, 29 chs		
18	0	Chauvet Intimidator Wash Zoom 350 IRC	Standard Lens, 14° - 58°		E.95	Advanced Mode, 29 chs		
19	0	Chauvet Intimidator Wash Zoom 350 IRC	Standard Lens, 14° - 58°		E.124	Advanced Mode, 29 chs		
20	0	Chauvet Intimidator Wash Zoom 350 IRC	Standard Lens, 14° - 58°		F.37	Advanced Mode, 29 chs		
21	0	Chauvet Intimidator Wash Zoom 350 IRC	Standard Lens, 14° - 58°		F.66	Advanced Mode, 29 chs		
22	0	Chauvet Intimidator Wash Zoom 350 IRC	Standard Lens, 14° - 58°		F.95	Advanced Mode, 29 chs		

23	0	Chauvet Intimidator Wash Zoom 350 IRC	Standard Lens, 14° - 58°	F.124	Advanced Mode, 29 chs
24	0	Chauvet Intimidator Wash Zoom 350 IRC	Standard Lens, 14° - 58°	C.131	Advanced Mode, 29 chs
25	0	Chauvet Intimidator Wash Zoom 350 IRC	Standard Lens, 14° - 58°	C.160	Advanced Mode, 29 chs
26	0	Chauvet COLORband PiX	Standard Lens, 20°	C.189	36 Channel Mode, 36 chs
27	0	Chauvet COLORband PiX	Standard Lens, 20°	C.225	36 Channel Mode, 36 chs
28	0	Chauvet COLORband PiX	Standard Lens, 20°	C.261	36 Channel Mode, 36 chs
29	0	Chauvet COLORband PiX	Standard Lens, 20°	C.297	36 Channel Mode, 36 chs
30	0	Chauvet COLORband PiX	Standard Lens, 20°	D.153	36 Channel Mode, 36 chs
31	0	Chauvet COLORband PiX	Standard Lens, 20°	D.189	36 Channel Mode, 36 chs
32	0	Chauvet COLORband PiX	Standard Lens, 20°	D.225	36 Channel Mode, 36 chs
33	0	Chauvet COLORband PiX	Standard Lens, 20°	D.261	36 Channel Mode, 36 chs
34	0	Chauvet COLORband PiX	Standard Lens, 20°	E.153	36 Channel Mode, 36 chs
35	0	Chauvet COLORband PiX	Standard Lens, 20°	E.189	36 Channel Mode, 36 chs
36	0	Chauvet COLORband PiX	Standard Lens, 20°	E.225	36 Channel Mode, 36 chs
37	0	Chauvet COLORband PiX	Standard Lens, 20°	E.261	36 Channel Mode, 36 chs
38	0	Chauvet COLORband PiX	Standard Lens, 20°	F.153	36 Channel Mode, 36 chs
39	0	Chauvet COLORband PiX	Standard Lens, 20°	F.189	36 Channel Mode, 36 chs
40	0	Chauvet COLORband PiX	Standard Lens, 20°	F.225	36 Channel Mode, 36 chs
41	0	Chauvet COLORband PiX	Standard Lens, 20°	F.261	36 Channel Mode, 36 chs
42	0	Chauvet COLORband PiX	Standard Lens, 20°	C.333	36 Channel Mode, 36 chs
43	0	Chauvet COLORband PiX	Standard Lens, 20°	C.369	36 Channel Mode, 36 chs
44	0	Chauvet COLORband PiX	Standard Lens, 20°	C.405	36 Channel Mode, 36 chs
45	0	Chauvet COLORband PiX	Standard Lens, 20°	C.441	36 Channel Mode, 36 chs
46	0	Elation CUEPIX Blinder WW4 (CUE242)	Standard Lens, 100°	C.1	Mode 6, 9 chs
47	0	Elation CUEPIX Blinder WW4 (CUE242)	Standard Lens, 100°	D.1	Mode 6, 9 chs
48	0	Elation CUEPIX Blinder WW4	Standard Lens,	E.1	Mode 6, 9 chs

		(CUE242)	100°		
49	0	Elation CUEPIX Blinder WW4 (CUE242)	Standard Lens, 100°	F.1	Mode 6, 9 chs
50	0	Elation CUEPIX Blinder WW4 (CUE242)	Standard Lens, 100°	C.10	Mode 6, 9 chs
51	0	Elation Platinum Spot 5R Pro (EPS620)	Standard, 11° - 42°	G.1	Standard Mode, 23 chs
52	0	Elation Platinum Spot 5R Pro (EPS620)	Standard, 11° - 42°	G.24	Standard Mode, 23 chs
53	0	Elation Platinum Spot 5R Pro (EPS620)	Standard, 11° - 42°	G.47	Standard Mode, 23 chs
54	0	Elation Platinum Spot 5R Pro (EPS620)	Standard, 11° - 42°	G.70	Standard Mode, 23 chs
55	0	Elation Platinum Spot 5R Pro (EPS620)	Standard, 11° - 42°	G.93	Standard Mode, 23 chs
56	0	Elation Platinum Spot 5R Pro (EPS620)	Standard, 11° - 42°	G.116	Standard Mode, 23 chs
57	0	Elation Platinum Beam 5R (EPB619)	Standard, 2.5°	G.139	Standard Mode, 13 chs
58	0	Elation Platinum Beam 5R (EPB619)	Standard, 2.5°	G.152	Standard Mode, 13 chs
59	0	Elation Platinum Beam 5R (EPB619)	Standard, 2.5°	G.165	Standard Mode, 13 chs
60	0	Elation Platinum Beam 5R (EPB619)	Standard, 2.5°	G.178	Standard Mode, 13 chs
61	0	Elation Platinum Beam 5R (EPB619)	Standard, 2.5°	G.191	Standard Mode, 13 chs
62	0	Elation Platinum Beam 5R (EPB619)	Standard, 2.5°	G.204	Standard Mode, 13 chs
63	0	Elation Platinum Beam 5R (EPB619)	Standard, 2.5°	G.217	Standard Mode, 13 chs
64	0	Elation Platinum Beam 5R (EPB619)	Standard, 2.5°	G.230	Standard Mode, 13 chs
65	0	Elation CUEPIX Blinder WW4 (CUE242)	Standard Lens, 100°	G.243	Mode 6, 9 chs
66	0	Elation CUEPIX Blinder WW4 (CUE242)	Standard Lens, 100°	G.252	Mode 6, 9 chs
67	0	Elation CUEPIX Blinder WW4 (CUE242)	Standard Lens, 100°	G.261	Mode 6, 9 chs
68	0	Chauvet Par 38	Standard Lens, 42°	A.297	Standard Mode, 1 ch
69	0	Chauvet Par 38	Standard Lens, 42°	A.298	Standard Mode, 1 ch
70	0	Chauvet Par 38	Standard Lens, 42°	A.299	Standard Mode, 1 ch
71	0	Chauvet Par 38	Standard Lens, 42°	A.300	Standard Mode, 1 ch
72	0	ETC Source Four PAR EA	MFL 230, 28°	A.170	Control, 1 ch

73	0	ETC Source Four PAR EA	MFL 230, 28°	A.170	Control, 1 ch
74	0	ETC Source Four PAR EA	MFL 230, 28°	A.250	Control, 1 ch
75	0	ETC Source Four PAR EA	MFL 230, 28°	A.250	Control, 1 ch
76	0	Blizzard Lighting ToughPAR RGBAW	36 x 1W LEDs Standard Lens, 15°	B.81	10 Channel Mode, 10 chs
77	0	Blizzard Lighting ToughPAR RGBAW	36 x 1W LEDs Standard Lens, 15°	B.91	10 Channel Mode, 10 chs
78	0	Blizzard Lighting ToughPAR RGBAW	36 x 1W LEDs Standard Lens, 15°	B.101	10 Channel Mode, 10 chs
79	0	Blizzard Lighting ToughPAR RGBAW	36 x 1W LEDs Standard Lens, 15°	B.111	10 Channel Mode, 10 chs
80	0	Blizzard Lighting ToughPAR RGBAW	36 x 1W LEDs Standard Lens, 15°	B.121	10 Channel Mode, 10 chs
81	0	Blizzard Lighting ToughPAR RGBAW	36 x 1W LEDs Standard Lens, 15°	B.211	10 Channel Mode, 10 chs
82	0	Blizzard Lighting ToughPAR RGBAW	36 x 1W LEDs Standard Lens, 15°	B.221	10 Channel Mode, 10 chs
83	0	Blizzard Lighting ToughPAR RGBAW	36 x 1W LEDs Standard Lens, 15°	B.131	10 Channel Mode, 10 chs
84	0	Blizzard Lighting ToughPAR RGBAW	36 x 1W LEDs Standard Lens, 15°	B.141	10 Channel Mode, 10 chs
85	0	Blizzard Lighting ToughPAR RGBAW	36 x 1W LEDs Standard Lens, 15°	B.151	10 Channel Mode, 10 chs
86	0	Blizzard Lighting ToughPAR RGBAW	36 x 1W LEDs Standard Lens, 15°	B.161	10 Channel Mode, 10 chs
87	0	Blizzard Lighting ToughPAR RGBAW	36 x 1W LEDs Standard Lens, 15°	B.201	10 Channel Mode, 10 chs
88	0	Blizzard Lighting ToughPAR RGBAW	36 x 1W LEDs Standard Lens, 15°	B.191	10 Channel Mode, 10 chs
89	0	Blizzard Lighting ToughPAR RGBAW	36 x 1W LEDs Standard Lens, 15°	B.181	10 Channel Mode, 10 chs
90	0	Blizzard Lighting ToughPAR RGBAW	36 x 1W LEDs Standard Lens, 15°	B.171	10 Channel Mode, 10 chs
91	0	ETC Source Four 19° (419)	HPL 750/115, 19°	A.45	Control, 1 ch
92	0	ETC Source Four 19° (419)	HPL 750/115, 19°	A.46	Control, 1 ch

93	0	ETC Source Four 19° (419)	HPL 575/115, 19°	A.130	Control, 1 ch
94	0	ETC Source Four 19° (419)	HPL 575/115, 19°	A.131	Control, 1 ch
95	0	ETC Source Four 19° (419)	HPL 575/115, 19°	A.165	Control, 1 ch
96	0	ETC Source Four 19° (419)	HPL 575/115, 19°	A.164	Control, 1 ch

---